

# Chlorine Dosing Systems



**ECL Hyprolyser® Compact Series 25, 50, 100g/h**  
 Ideal for smaller commercial pools such as hotels, schools, spas and hydrotherapy facilities, and for many building services and industrial uses, the new Hyprolyser® Compact modular & skid mounted range brings all the benefits of on-site hypochlorite generation well within the reach of virtually any commercial or residential pool owner. Modular systems allow maximum flexibility for restricted installation space. Skid mounted systems provide a completely assembled package, pre-commissioned, for quick and easy installation.

Complete sizing service available on request.



Matchcode order system Hyprolyser® Compact - MODULAR Systems			
Generator capacity			
C1	Compact 25 - 25g/h electrolytic chlorine generation unit		
C2	Compact 50 - 50g/h electrolytic chlorine generation unit		
C3	Compact 100 - 100g/h electrolytic chlorine generation unit		
System configuration			
M	MODULAR system configuration		
Softener equipment options - cold water supply			
F1	Automatic ion-exchange softener kit		
F2	Filter cartridge kit (97,000mg TDS CaCO3 capacity)	Only available with Compact 25 generator	
F3	Filter cartridge kit (292,000mg TDS CaCO3 capacity)		
F4	None - softened water available on site		
Ventilation pack			
1	Air blower & ventilation kit		
0	None optional only on Compact 25 generator - site Risk Assessment required		
Product storage/capacity options			
T1	50 litre product storage tank & level control assembly kit		
T2	100 litre product storage tank & level control assembly kit		
T3	200 litre product storage tank & level control assembly kit		
T4	Special/Custom design product storage tank & level control assembly kit		
Power supply options			
V1	110V ac 50Hz Ø1		
V2	240V ac 50Hz Ø1		standard
C1	M	F1	1
T1	V2		Order Example

Matchcode order system Hyprolyser® Compact - SKID Systems			
Generator capacity			
C1	Compact 25 - 25g/h electrolytic chlorine generation unit		
C2	Compact 50 - 50g/h electrolytic chlorine generation unit		
C3	Compact 100 - 100g/h electrolytic chlorine generation unit		
System configuration			
S	SKID system configuration		
Softener equipment options - cold water supply			
F1	Automatic ion-exchange softener kit		
F2	Filter cartridge kit (97,000mg TDS CaCO3 capacity)	Only available with Compact 25 generator	
F3	Filter cartridge kit (292,000mg TDS CaCO3 capacity)		
F4	None - softened water available on site		
Ventilation pack			
1	Air blower & ventilation kit		
Product storage/capacity options			
T3	200 litre product storage tank & level control assembly kit		
Power supply options			
V1	110V ac 50Hz Ø1		
V2	240V ac 50Hz Ø1		
C1	S	F1	1
T3	V2		Order Example